



249.00 EUR  
incl. 19% VAT, plus [shipping](#)

Support:  [Specifications \[EN\]](#)

- AMD Brazos eOntario + Hudson E1 Chipset
- Support AMD eOntario (G-Series) Dual core 1.6GHz APU
- Support DirectX 11 3D Graphics Acceleration
- Support 5 \* Serial ATA3 (6Gb/s) Devices with RAID 0,1,5,10 & 1 \* mSATA
- Support DDR3 800-1066 Single Channel 64-bit, up to 8GB
- Integrated VIA VT1705 HD Audio CODEC with 6-CH
- 1 \* 24 bit Dual Channel LVDS header
- Support DVI-D/HDMI Output
- Supports 2 \* Realtek RT8111E Gigabit LAN
- Support CPU Smart FAN
- Compliance with ErP standard
- ITX Form Factor(170mm x 170mm)
- CPU
- Chipset
- Memory
- Expansion Slots
- Storage
- Audio
- Support AMD eOntario (G-Series) T56N Dual core 1.6GHz APU
- AMD Brazos eOntario + Hudson E1 Chipset
- 2 \* SODIMM Sockets for un-buffered Single Channel 64-bit DDR3 800-1066 SDRAM up to 8 GB
- 1 \* 32-bit PCI slot
- 1 \* Mini PCI-E
- 5 \* Serial ATA3 6Gb/s connectors support HDD with RAID 0, 1, 5,10 functions
- 1 \* mSATA socket
- VIA VT1705 6-Channel HD Audio CODEC

- Ethernet LAN
  - USB
  - Rear Panel I / O
  - Internal I / O
  - BIOS
  - Certificate
  - Functional
  - Temperature
  - Form Factor
- 2 \* Realtek RTL8111E PCI-E LAN chip for Gigabit LAN
  - Embedded 10 \* USB 2.0/1.1
  - 6 \* USB 2.0/1.1 ports
  - 1 \* PS2 KB/MS port
  - 2 \* RJ-45 ports
  - 1 \* Audio I / O port
  - 1 \* VGA port
  - 1 \* DVI-D port
  - 1 \* HDMI port
  - 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
  - CPU / Chassis Fan connectors;
  - 1 \* 24-pin ATX Power connector
  - 1 \* 24 bit Dual Channel LVDS header
  - 1 \* COM Port & 1 \* GPIO header
  - 1 \* CIR header
  - AMI 16MB SPI Flash ROM
  - CE,FCC,RoHS,Eup
  - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
  - Operating within 0~50 centigrade
  - Storage within -20-85 centigrade
  - Mini ITX Form Factor(170mmx170mm)

**Product Accessories**

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield