



659.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel® BayTrail-M N2930 Quad Core Processor
- 2 \* SO-DIMM DDR3L 1333MHz up to 8GB
- 2 x Gigabit LAN , 2 x Bypass Gigabit LAN , 4 x Expansion Card Gigabit LAN
- Form Factor : 430 x 251 x 44 mm
- AC 90~240V\_200W FLEX Power

|                 |                                                                                                                                                                                                                                                                                                                                             |                                  |                                      |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|--------------------------------------|
| MB Model        | – JNF9HB-2930 / Mini-ITX                                                                                                                                                                                                                                                                                                                    |                                  |                                      |
| Part No         | Standard                                                                                                                                                                                                                                                                                                                                    | 4 ports GbE PCI-E expansion card | 2 Pairs of Bypass LAN expansion card |
|                 | – HBJC153F9HB-2930-B                                                                                                                                                                                                                                                                                                                        | – HBJC153F9HB-2930G4             | – HBJC153F9HB-2930B4                 |
| BIOS            | – AMI 64MB SMT Flash ROM                                                                                                                                                                                                                                                                                                                    |                                  |                                      |
| CPU/Chipset     | – Intel® Bay Trail-M N2930 SoC Processor (Default)                                                                                                                                                                                                                                                                                          |                                  |                                      |
| Memory          | Support 2 * DDR3L 1333/1066MHz SO-DIMM up to 8GB                                                                                                                                                                                                                                                                                            |                                  |                                      |
| Storage         | – Support 2 * 2.5" SATA Drive bay (only support 2.5" HDD with a height ≤ 10mm)<br>– Support 1 * full-size mSATA/Mini-PCI Express shared slot                                                                                                                                                                                                |                                  |                                      |
| Expansion       | – 1 * full size Mini-PCIe<br>– 1 * SIM card slot<br>– Support TPM (optional)                                                                                                                                                                                                                                                                |                                  |                                      |
| Network         | – 4 * Intel i211AT GbE (1 pair support ByPass GbE)<br>– 1 * full-size Mini-PCIe slot (802.11 b/g/n + BT 4.0 installed in WiFi model)                                                                                                                                                                                                        |                                  |                                      |
| Rear Panel I/O  | – 1 * Power switch<br>– AC input / 1U FLEX 200W Power build in                                                                                                                                                                                                                                                                              |                                  |                                      |
| Front Panel I/O | – 4 * RJ45 (1 pair support ByPass GbE)<br>– 1 * USB3.0)<br>– 1 * USB2.0)<br>– 1 * VGA)<br>– 2 * COM)<br>– 1 * PW LED, 1 * Alarm LED)<br>– 1 * GPIO (Not assembled when shipped, wire placed in the parts box))<br>– 4 ports GbE PCIe expansion card: HBJC153F9HB-2930G4)<br>– 2 pairs of Bypass LAN PCIe expansion card: HBJC153F9HB-2930B4 |                                  |                                      |
| Power Source    | – 1U FLEX 200W Power build in<br>– AC 90~240V input                                                                                                                                                                                                                                                                                         |                                  |                                      |
| Compliance      | – CE, FCC, RoHS                                                                                                                                                                                                                                                                                                                             |                                  |                                      |
| Temperature     | – Operating temperature: 0 ~ 40° C<br>– Storage Temperature: -10 ~ 70° C                                                                                                                                                                                                                                                                    |                                  |                                      |
| Dimensions      | – 430 (W) x 252 (D) x 44 (H) mm                                                                                                                                                                                                                                                                                                             |                                  |                                      |
| Packing         | – Net Weight: 4.2KG<br>– Gross Weight: 5KG<br>– Color Box dimension: 560 (W) * 400 (D) * 380 (H) mm                                                                                                                                                                                                                                         |                                  |                                      |

---

|            |                                             |
|------------|---------------------------------------------|
| OS Support | – Windows 7, Windows 8.1, Windows 10, Linux |
| Warranty   | – 2 Years limited warranty                  |